

# LB1698

\*\*\*\*\*

DESIGNATION - D 94  
PID - LB1698  
STATE/COUNTY- IN/TIPPECANOE  
USGS QUAD - WESTPOINT (1962)

## \*CURRENT SURVEY CONTROL

* NAD 83(1986)-	40 20 19.	(N)	087 03 11.	(W)	SCALED
* NAVD 88	-	195.769	(meters)	642.29	(feet) ADJUSTED
<hr/>					
GEOID HEIGHT-	-33.42	(meters)			GEOID03
DYNAMIC HT -	195.673	(meters)	641.97	(feet)	COMP
MODELED GRAV-	980,132.6	(mgal)			NAVD 88
<hr/>					
VERT ORDER -	SECOND	CLASS	0		

.The horizontal coordinates were scaled from a topographic map and have

.an estimated accuracy of +/- 6 seconds.

.The orthometric height was determined by differential leveling and adjusted in June 1991.

.The geoid height was determined by GEOID03.

.The dynamic height is computed by dividing the NAVD 88 geopotential number by the normal gravity value computed on the Geodetic Reference System of 1980 (GRS 80) ellipsoid at 45 degrees latitude (g = 980.6199 gals.).

.The modeled gravity was interpolated from observed gravity values.

;  
;SPC IN W - North East Units Estimated Accuracy  
Scaled) 565,120. 902,570. MT (+/- 180 meters

## SUPERSEDED SURVEY CONTROL

NGVD 29 (??/??/92) 195.852 (m) 642.56 (f) ADJ UNCH 2  
0

.Superseded values are not recommended for survey control.

.NGS no longer adjusts projects to the NAD 27 or NGVD 29 datums.

.[See file dsdata.txt](#) to determine how the superseded data were derived.

\_U.S. NATIONAL GRID SPATIAL ADDRESS: 16TDK954653(NAD 83)  
\_MARKER: DB = BENCH MARK DISK  
\_SETTING: 30 = SET IN A LIGHT STRUCTURE  
\_SP\_SET: CULVERT  
\_STAMPING: D 94 1946  
\_STABILITY: D = MARK OF QUESTIONABLE OR UNKNOWN STABILITY

HISTORY	- Date	Condition	Report By
HISTORY	- 1946	MONUMENTED	CGS

STATION DESCRIPTION

DESCRIBED BY COAST AND GEODETIC SURVEY 1946

0.9 MI S FROM WEST POINT.

ABOUT 0.9 MILE SOUTH ALONG STATE HIGHWAY 25 FROM THE WAYNE TOWNSHIP SCHOOL AT WEST POINT, SET IN THE TOP OF THE NORTH END OF THE EAST HEAD WALL OF A 3 FOOT CONCRETE BOX CULVERT, 51 FEET SOUTH OF THE CENTER LINE OF A DRIVE WAY LEADING TO A HOUSE, ABOUT 125 FEET SOUTHWEST OF THE HOUSE, 24 FEET SOUTHWEST OF A TWIN ASH TREE, 23.7 FEET EAST OF THE CENTER LINE OF THE HIGHWAY, 1.2 FEET SOUTH OF THE NORTH END OF THE HEAD WALL, AND ABOUT 2 FEET BELOW THE HIGHWAY. A STANDARD DISK, STAMPED D 94 1946.

1 National Geodetic Survey, Retrieval Date = DECEMBER 21, 2007

F-32

Wayne Township, SE of Section 5 in Burnete's Reserve at the mouth of Flint Creek, 22-6, 0.9 miles south along State Road 25 from the Wayne Township School at Westpoint, 125 feet southwest of a house, ~~51 feet southwest of a house,~~ <sup>5407</sup> <sub>SR25</sub> ~~51~~ feet south of the centerline of a driveway leading to the house, 23.7 feet east of the centerline of the highway, a 3 foot box culvert, 1.2 feet south of the north end of the east end of the east headwall, about 2 feet lower than the highway. A standard disk, stamped "D 94 1946."

Recovered 7/80 Elevation 642.558

RECOVERED 8/87

RECOVERED 9.14.89

" Sept. 28, 1994 IN GOOD CONDITION  
 " 7/11/07 In Good Condition (MWF)